

BT-610 Bench-Top Particle Counter

The BT-610 is a compact battery operated particle counter with six selectable size channels, built-in printer, housed in a portable stainless steel case. Flow rate is 0.1 cfm (2.83 lpm) and is maintained with volumetric flow control for improved accuracy.

Key Features:

Simple Operation

The BT-610 has a large size display with very large characters, audible alarm, and internal printer that work together to verify particulate levels. If the particle count exceeds a pre-set limit, the audible alarm will beep, the screen display will flash, and the printer will print the alarm value. Two programmable count alarm limits may be set.

Convenient for Compliance

Comply with 21 CFR Part 11 with a password feature to prevent unauthorized changes to the user settings. ISO 21501-4 calibration is available for ISO 14644-1 compliance.

User Selectable Sizes

Each of the six channels may be individually set by the operator from 0.3 to 10 microns. Custom calibrations are not required.

Data Storage and Connectivity

The BT-610 stores over 8,000 sample events. Sample history events can be viewed or printed and downloaded to a computer using Comet software or simple ASCII terminal commands. Connectivity is built-in for both digital (RS-232, RS-485) and analog output (0-5 VDC). The BT-610 also includes USB interface, and a Memory Stick port.

Printer

The Printer has two modes of operation. Print Sample: prints sample data at the end of each sample including alarm, date, time and location. Recall Data: prints all sample data from first selected date and time to second selected date and time.

Portable Desk Top

The BT-610 provides 6 channels, built-in printer and battery operation in a compact stainless steel case. The built-in battery provides 24 hours of typical (intermittent) operation and 8 hours continuous operation. Connect the AC adapter/charger for longer operation and battery charging.

Temperature / Relative Humidity Option

A plug-and-play option can immediately add ambient temperature and relative humidity



capabilities to displayed and logged data.

Applications

- Clean-room Monitoring
- Medical Device Manufacturing
- Filter Testing
- Hospitals
- Food / Beverage
- Aerospace Assembly
- Paint Booths
- Cosmetic Manufacturing

Specifications

BT-610 Bench-Top Particle Counter

Interface	
Display	20 character x 4 line LCD
Keyboard	8 key membrane type
Performance PM	0.3µm - 10µm, 6 channels 0.3 µm, 0.5µm, 1.0µm, 2.0µm
Ranges	5.0µm and 10µm 0.1µm steps from 0.3µm - 2.0µm
Calibrated Sizes	0.5µm steps from 2.0µm - 10µm 0 – 3,000,000 particles
User Size Settings	per cubic foot (105,900 particle/L) ± 10% to calibration aerosol 0.3 µm 0.1 cfm (2.83 lpm) 1 to 999 seconds 0 to 999 seconds
Concentration Range	
Accuracy	
Sensitivity	
Flow Rate	
Sample Time Adjustable	
Hold Time Adjustable	
Electrical	
Light Source	Laser Diode, 90mW, 780 nm
Power	14.8V Li-Ion self-contained battery pack – Provides for 8 hours continuous use. Full recharge approximately 3 hours.
AC Adapter/Charger	Li-Ion Charger, 100 – 240 VAC to 16.8 VDC @ 1.8A USB,
Communications	RS-232 or RS-485
Standards	Meets ISO 21501-4. CE marked. ISO 9001 manufacturing facility.
Physical	
Weight	8 lb - 1.6 oz (3.67 kg)
Size	Height = 8.75" (22.2 cm) With Handle = 10.25"(26.0 cm) Width = 6.75" (17.1 cm) Depth = 8.5" (21.5 cm)
Environmental	
Operation Temperature	0° to +40°C
Storage Temperature	-20° to +60°C

Specifications are subject to change at any time.

SUPPLIED ACCESSORIES

Operation
Manual USB
Cable Comet
Software
Particle View Software
Battery Charger
Iso-kinetic Sample Probe
Zero Particulate Filter
Printer Paper - 2 Rolls
Calibration Certificate



OPTIONAL ACCESSORIES

RH & Temperature Probe
Flow Meter
Serial Cable
Particle View RT Software
ISO 21501-4 Calibration



Met One Instruments, Inc.

1600 Washington Blvd. Grants Pass, Oregon 97526 Phone: 541.471.7111

Sales: sales@metone.com | Service: service@metone.com | Website: www.metone.com

July 2020